

MARSHFIELD MOTOR SPEEDWAY LLC - 715-384-8325
2009 Junkyard Warrior Division 4-Cyl and V-6 OEM Fun Class

Safety:

- Must have fire extinguisher
- Must have Snell 85 helmet
- Must wear long pants and long sleeved shirt
- All flammable parts must be removed from car, nothing else
- Car must be American made
- Car to appear neatly, brightly painted and lettered, no offensive logos this is a family sport
- Body of car must appear street ready and recognizable by spectators as to what type of car it is. No wheelbases above 107"
- All glass but windshield must be removed. Lexan windshield highly recommended. No cracks allowed in windshield.
- All inner fenders and parts must remain intact. Bumpers must be on.
- If car is 4 door post, it may have a 4-point roll cage, all other bodies must have a 6 point roll cage 1 3/4" .095 thickness made of roll bar tubing, no muffler pipe allowed.
- 4 door post car may have a safe bucket seat with shoulder strap seat belts, 2 shoulder straps. All others must have racing harness seat belts.

Motors:

- No motors above 3810 cc, NO tolerance. No inline 6 cyl motors.
- 4-Cyl may have factory turbo only.
- Motors must match car for body style; as per A. Z. K. for example. American made cars only. Must have Made in USA sticker on door. No Dual Overhead Cam engines. No high performance engines.
- OEM parts only, no racing parts. All parts must have original manufacturers stamp. NO machine work of any type allowed.
- No compression on motor allowed above 150 psi after race. Test taken with track compression gauge.
- Fuel system must be original for year of vehicle. Carburetor for carburetor, injectors for injectors, no switching. Do not remove the fuel tank. Call the tech inspector if the fuel tank is behind the rear axle.

Suspension:

- Manufacturers only. No race parts, no machined parts, no traction devices added.
- 4" minimum ground clearance.

Weight: After race, 4-Cyl 2000 lbs, 6-cyl 2200 lbs. Must have 4-cyl or 6-cyl ID on it and readable by the scale person. Rear wheel drive cars must add 300 lbs to vehicle

Wheels & Tires: 7" maximum stock steel rims. 1" lug nuts. Front or rear wheel drive, no four wheel drives. Any 13", 14" or 15" tire, 60 series or narrower tires allowed.

Measurements: Taken with driver and all equipment in the car.

If you have questions call Jerry Parker at 715-964-2001 or e-mail to jugp@centurytel.net

This is a young new class of cars, if you have any ideas to make it better; Please contact **Jerry Parker** with your suggestions.

Before building a new car, please if you have any questions call Jerry Parker.

The track officials reserve the right to make necessary weight adjustments to keep racing competitive.